

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES


Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.



The Delphion
Integrated
View

Other Views:
[INPADOC](#)

Title: **JP7272717A2: MANUFACTURE OF FLAT TYPE NONAQUEOUS ELECTROLYTE BATTERY**

► [Want to see a more descriptive title highlighting what's new about this invention?](#)

Country: **JP Japan**
Kind: **A**

Inventor(s): **MIZUNO TOSHIO
IZUMI AKIHIDE
NISHIO MASATAKE
NOZUE TOMOHISA**

Applicant/Assignee: **FUJI ELELCTROCHEM CO LTD**



[News, Profiles, Stocks and More about this company](#)

Issued/Filed Dates: **Oct. 20, 1995 / March 31, 1994**

Application Number: **JP1994000063556**

IPC Class: **H01M 4/12; H01M 6/16;**

Priority Number(s): **March 31, 1994 JP1994000063556**

Abstract:




Purpose: To provide a manufacturing method for a flat type nonaqueous electrolyte battery capable of enhancing reaction efficiency of lithium and obtaining stable discharge performance by efficiently, accurately pressing for fixing lithium in the form of nearly complete round to the whole surface of a negative terminal.

Constitution: In the manufacturing method for a flat type nonaqueous electrolyte battery fabricated by using a negative electrode 2 formed by pressing lithium 2b serving as a negative active material against a disk-like negative terminal 2a, a chip of lithium 2b obtained by cutting a rod is temporarily pressed near the center of the negative terminal 2a. The chip is temporarily molded by 1/2-1/4 of the chip thickness with a pressing jig K with a recessed surface to form an almost round projection, then the chip is pressed by 1/6 or less of the original thickness with a pressing jig G with flat surface to press against the negative terminal 2a to form the negative electrode 2. Before the lithium 2b is temporarily molded in the form of almost round projection, a die lubricant 6 stable to an electrolyte such as propylene carbonate (PC) and liquid paraffin is preferably applied to the surface of the lithium 2b coming in contact with the pressing jig K.

COPYRIGHT: (C)1995,JPO

► [See a clear and precise summary of the whole patent, in understandable terms.](#)

Family: [Show known family members](#)



View
Image

1 page

Other Abstract Info: CHEMABS 124(06)061599C CAN124(06)061599C DERABS C96-013923
DERC96-013923

Foreign References: No patents reference this one



Nominate this
for the Gallery...

[Subscribe](#) | [Privacy Policy](#) | [Terms & Conditions](#) | [FAQ](#) | [Site Map](#) | [Help](#) | [Contact Us](#)

© 1997 - 2002 Delphion Inc.



(19)

(11) Publication number: **07272717 A**

Generated Document.

PATENT ABSTRACTS OF JAPAN(21) Application number: **06063556**(51) Intl. Cl.: **H01M 4/12 H01M 6/16**(22) Application date: **31.03.94**

(30) Priority: (43) Date of application publication: 20.10.95 (84) Designated contracting states:	(71) Applicant: FUJI ELELCTROCHEM CO LTD (72) Inventor: MIZUNO TOSHIO IZUMI AKIHIDE NISHIO MASATAKE NOZUE TOMOHISA (74) Representative:
--	---

(54) MANUFACTURE OF FLAT TYPE NONAQUEOUS ELECTROLYTE BATTERY

(57) Abstract:

PURPOSE: To provide a manufacturing method for a flat type nonaqueous electrolyte battery capable of enhancing reaction efficiency of lithium and obtaining stable discharge performance by efficiently, accurately pressing for fixing lithium in the form of nearly complete round to the whole surface of a negative terminal.

CONSTITUTION: In the manufacturing method for a flat type nonaqueous electrolyte battery fabricated by using a negative electrode 2 formed by pressing lithium 2b serving as a negative active material against a disk-like negative terminal 2a, a chip of lithium 2b obtained by cutting a rod is temporarily pressed near the center of the negative terminal 2a. The chip is temporarily molded by 1/2-1/4 of the chip thickness with a pressing jig K with a recessed surface to form an almost round projection, then the chip

is pressed by 1/6 or less of the original thickness with a pressing jig G with flat surface to press against the negative terminal 2a to form the negative electrode 2. Before the lithium 2b is temporarily molded in the form of almost round projection, a die lubricant 6 stable to an electrolyte such as propylene carbonate (PC) and liquid paraffin is preferably applied to the surface of the lithium 2b coming in contact with the pressing jig K.

COPYRIGHT: (C)1995,JPO

